



HOLDRITE VARIABLE STRUT CLAMP

FIG. #257-P

411 BURNHAM ST.
 P.O. BOX 280186
 EAST HARTFORD, CT 06108
 TEL (860) 289-0285 FAX (860) 282-1487
 TOLL FREE 1-800-969-0285

SERVICE: STONG, SOUND RATED VARIABLE CLOSURE CLAMP. TWO ACOUSTICAL INSERTS ISOLATE THE PIPE FROM THE SUPPORT STRUCTURE, REDUCING PIPING NOISE AND VIBRATION, WHILE ALLOWING NORMAL PIPE EXPANSION AND CONTRACTION.

APPLICATION: CLAMPS SUPPORTS UP TO 1" CTS TUBING SIZES. SUPPORTS COPPER, PEX, CPVC TUBING, CONDUIT, ETC. SUPPORTS 3/8" TO 2" TUBING/PIPING WITH TOP MOUNT LOAD RATING OF UP TO 200 POUNDS. LOAD RATING SUSPENDED 25LBS.

TEMPERATURE RANGE: -10°F TO 180° F

NO TOOLS REQUIRED AND ELIMINATES NEED FOR OVER 20 STRUT CLAMP SKUs.

INCLUDES ISOLATION PADS TO MINIMIZE NOISE AND VIBRATION, LAB TESTED.

PROVIDES DISSIMILAR METAL ISOLATION.

FRAMEWORK COMPLIES WITH UL 94V-2 FIRE RATING.



STRUT CLAMP #257-P



| Model # | Size | For Pipe Size (s) | Box Qty |
|---------|-----------------|-------------------|---------|
| 257-P | 2-1/2" x 2-7/8" | 3/8" - 1" CTS | 50 |

SUBMITTAL INFORMATION

| | | | |
|-----------------|----------|----------------|--|
| CUSTOMER: | | APPROVAL STAMP | |
| PROJECT NAME: | | | |
| PROJECT NUMBER: | SECTION: | | |
| PARAGRAPH: | OTHER: | | |

REV: A

2008